

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**die:master spacer varnish blue 1956 0300**

Revision date: 25.08.2021

Product code: 19560300

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

die:master spacer varnish blue 1956 0300

**Further trade names**

contained in:

1956 0900 die:master Set blue

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

One-pack coating

**Uses advised against**

No information available.

**1.3. Details of the supplier of the safety data sheet**

Company name: Renfert GmbH

Street: Untere Giesswiesen 2

Place: D-78247 Hilzingen

Telephone: +49 7731 8208-0

Telefax: +49 7731 8208-70

e-mail: info@renfert.com

Contact person: Frau Andris

e-mail: silke.andris@renfert.com

Internet: www.renfert.com

**1.4. Emergency telephone number:**

GB: 0044 151 951 3317 (Health and Safety Executive (HSE) Chemicals) | USA: 800-222-1222 (National Poison Control number) | CA: British Columbia: 800-567-8911 or 604-682-5050 Alberta: 1-800-332-1414 or 944-1414 Saskatchewan: 1-866-454-1212 Manitoba: 1-855-776-4766 Ontario: 1-800-268-9017 Quebec: 1-800-463-5060 New Brunswick: 911 Newfoundland: 1-866-727-1110 Northwest Territories: 1-800-332-1414 Nova Scotia: 1-800-565-8161 | AU: 13 11 26 | ZA: 021 938 6084 (Office Hours) or 021 931 6129 (24 Hours)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard components for labelling**

butanone

pentan-3-one

n-butyl acetate

**Signal word:**

Danger

**Pictograms:****Hazard statements**

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

H335

May cause respiratory irritation.

H336

May cause drowsiness or dizziness.

**Precautionary statements**

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261

Avoid breathing dust/fume/gas/mist/vapours/spray.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**die:master spacer varnish blue 1956 0300**

Revision date: 25.08.2021

Product code: 19560300

Page 2 of 8

P280 Wear protective gloves and eye/face protection.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

**Special labelling of certain mixtures**

EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Labelling of packages where the contents do not exceed 125 ml****Signal word:** Danger**Pictograms:****2.3. Other hazards**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

One-pack coating

**Hazardous components**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
78-93-3	butanone			20 - 35%
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
96-22-0	pentan-3-one			20 - 35%
	202-490-3	606-006-00-5	01-2119531111-60	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3, STOT SE 3; H225 H319 H335 H336 EUH066			
123-86-4	n-butyl acetate			5 - 20%
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
13463-67-7	Titanium dioxide			3 - 10%
	236-675-5		01-2119489379-17	

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated, saturated clothing immediately.  
Get medical advice/attention if you feel unwell.

**After inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**After contact with skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

**After contact with eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**After ingestion**

Rinse mouth immediately and drink plenty of water. When in doubt or if symptoms are observed, get medical advice.

**4.2. Most important symptoms and effects, both acute and delayed**

The following symptoms may occur: Vapours may cause drowsiness and dizziness. Processing vapours can irritate the respiratory tracts, skin and eyes. Repeated exposure may cause skin dryness or cracking.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**die:master spacer varnish blue 1956 0300**

Revision date: 25.08.2021

Product code: 19560300

Page 3 of 8

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Extinguishing powder, Carbon dioxide (CO<sub>2</sub>), alcohol resistant foam, Water spray jet

##### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

Vapours can form explosive mixtures with air.

Thermal decomposition can lead to the escape of irritating gases and vapours.

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### General measures

Provide adequate ventilation.

Use personal protection equipment.

Remove all sources of ignition.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

##### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Use only in well-ventilated areas.

Avoid contact with eyes and skin.

When using do not eat, drink or smoke.

##### Advice on protection against fire and explosion

Vapours can form explosive mixtures with air.

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

##### Further information on handling

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

#### 7.3. Specific end use(s)

Please refer to our internet website for more information: [www.renfert.com](http://www.renfert.com)

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**die:master spacer varnish blue 1956 0300**

Revision date: 25.08.2021

Product code: 19560300

Page 4 of 8

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
96-22-0	Pentan-3-one	200	716		TWA (8 h)	WEL
		250	895		STEL (15 min)	WEL
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL

**Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

**8.2. Exposure controls****Appropriate engineering controls**

Safe handling: see section 7

**Protective and hygiene measures**

Do not breathe vapour.

Avoid contact with skin, eyes and clothes.

Wash hands before breaks and after work.

Keep away from food, drink and animal feedingstuffs.

**Eye/face protection**

Wear eye/face protection.

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Suitable material: NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

Thickness of the glove material: 0,5 mm

Breakthrough time: &gt;= 60 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

**Respiratory protection**

Use only in well-ventilated areas.

Usually no personal respirative protection necessary.

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state: Liquid  
 Colour: blue  
 Odour: characteristic

**Test method**

pH-Value: not applicable

**Changes in the physical state**

Melting point: not determined

Boiling point or initial boiling point and boiling range: 79 °C

Flash point: &lt; 0 °C DIN 51755 (cc)

**Flammability**

Solid/Liquid: not applicable

Gas: not applicable

**Explosive properties**

not explosive.

Vapours can form explosive mixtures with air.



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**die:master spacer varnish blue 1956 0300**

Revision date: 25.08.2021

Product code: 19560300

Page 5 of 8

Lower explosion limits:	1,2 vol. %
Upper explosion limits:	11,5 vol. %
Auto-ignition temperature:	370 °C
<b>Self-ignition temperature</b>	
Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined
Vapour pressure: (at 20 °C)	105 hPa
Density (at 20 °C):	0,80 - 1,10 g/cm <sup>3</sup>
Water solubility:	Immiscible
Partition coefficient n-octanol/water:	not determined
Viscosity / dynamic:	not determined
Viscosity / kinematic:	not determined
Evaporation rate:	not determined

## 9.2. Other information

No data available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Vapours can form explosive mixtures with air.

### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **Irritation and corrosivity**

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### **Sensitising effects**

Based on available data, the classification criteria are not met.

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### **STOT-single exposure**

May cause respiratory irritation. (pentan-3-one)

May cause drowsiness or dizziness. (butanone; pentan-3-one)

#### **STOT-repeated exposure**

Repeated exposure may cause skin dryness or cracking.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

#### **Endocrine disrupting properties**

No information available.

#### **Further information**

The product has not been tested. The statement is derived from the properties of the single components.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

There are no data available on the mixture itself.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**die:master spacer varnish blue 1956 0300**

Revision date: 25.08.2021

Product code: 19560300

Page 6 of 8

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

CAS No	Chemical name	Value	d	Source
	Method			
	Evaluation			
78-93-3	butanone			
	OECD 301D	98 %	28	
	Readily biodegradable (according to OECD criteria).			

**12.3. Bioaccumulative potential**

No indication of bioaccumulation potential.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
96-22-0	pentan-3-one	0,82

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

There are no data available on the mixture itself.

**12.7. Other adverse effects**

No information available.

**Further information**

The product has not been tested. The statement is derived from the properties of the single components. Do not allow uncontrolled discharge of product into the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Send to a hazardous waste incinerator facility under observation of official regulations.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**List of Wastes Code - residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number:</b>	UN 1263
<b>14.2. UN proper shipping name:</b>	FARBE
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3

**Marine transport (IMDG)**

<b>14.1. UN number:</b>	UN 1263
<b>14.2. UN proper shipping name:</b>	PAINT
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**die:master spacer varnish blue 1956 0300**

Revision date: 25.08.2021

Product code: 19560300

Page 7 of 8



Marine pollutant: no

**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number:** UN 1263**14.2. UN proper shipping name:** PAINT**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Further information: see section 6, 7, 8

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

2004/42/EC (VOC): 1956-0300: 69,6%

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

**Additional information**

REGULATION (EC) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on substances that deplete the ozone layer: not applicable

REGULATION (EU) 2019/1021 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on persistent organic pollutants

: not applicable

REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the export and import of hazardous chemicals: not applicable

**SECTION 16: Other information****Abbreviations and acronyms**

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LD50: lethal dose, 50%

LC50: lethal concentration, 50%

EC50: half maximal effective concentration

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

VOC: volatile organic compound(s)

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**die:master spacer varnish blue 1956 0300**

Revision date: 25.08.2021

Product code: 19560300

Page 8 of 8

**Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Restricted to professional users.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

Revision date: 27.11.2020

**die:master duo 1956 0600**

Product code: 19560600

Page 1 of 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

die:master duo 1956 0600

**Further trade names**

contained in:

1956 0800 die:master Set red  
1956 0900 die:master Set blue  
1956 1000 die:master Set gold/silver  
1957 1000 die:master Set ivory  
1957 2000 die:master Set aqua

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

One-pack coating

**Uses advised against**

No information available.

**1.3. Details of the supplier of the safety data sheet**

Company name: Renfert GmbH  
Street: Untere Giesswiesen 2  
Place: D-78247 Hilzingen  
Telephone: +49 7731 8208-0 Telefax: +49 7731 8208-70  
e-mail: info@renfert.com  
Contact person: Frau Andris  
e-mail: silke.andris@renfert.com  
Internet: www.renfert.com

**1.4. Emergency telephone number:**

GB: 0044 151 951 3317 (Health and Safety Executive (HSE) Chemicals) | USA: 800-222-1222 (National Poison Control number) | CA: British Columbia: 800-567-8911 or 604-682-5050 Alberta: 1-800-332-1414 or 944-1414 Saskatchewan: 1-866-454-1212 Manitoba: 1-855-776-4766 Ontario: 1-800-268-9017 Quebec: 1-800-463-5060 New Brunswick: 911 New Foundland: 1-866-727-1110 Northwest Territories: 1-800-332-1414 Nova Scotia: 1-800-565-8161 | AU: 13 11 26 | ZA: 021 938 6084 (Office Hours) or 021 931 6129 (24 Hours)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard components for labelling**

butanone

n-butyl acetate

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**die:master duo 1956 0600**

Revision date: 27.11.2020

Product code: 19560600

Page 2 of 9

**Signal word:** Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P280 Wear protective gloves and eye/face protection.  
 P337+P313 If eye irritation persists: Get medical advice/attention.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.

**Special labelling of certain mixtures**

EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3. Other hazards**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

One-pack coating

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
78-93-3	butanone			< 75 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
123-86-4	n-butyl acetate			10 - 25 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated, saturated clothing immediately.

**After inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**After contact with skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**die:master duo 1956 0600**

Revision date: 27.11.2020

Product code: 19560600

Page 3 of 9

**After contact with eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**After ingestion**

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. When in doubt or if symptoms are observed, get medical advice.

**4.2. Most important symptoms and effects, both acute and delayed**

The following symptoms may occur: Vapours may cause drowsiness and dizziness. Processing vapours can irritate the respiratory tracts, skin and eyes. Repeated exposure may cause skin dryness or cracking.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Extinguishing powder, Carbon dioxide (CO<sub>2</sub>), alcohol resistant foam, Water spray jet

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Vapours can form explosive mixtures with air.

Thermal decomposition can lead to the escape of irritating gases and vapours.

**5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General measures**

Provide adequate ventilation.

Use personal protection equipment.

Remove all sources of ignition.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

**6.3. Methods and material for containment and cleaning up****Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Use only in well-ventilated areas.

Avoid contact with eyes and skin.

When using do not eat, drink or smoke.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**die:master duo 1956 0600**

Revision date: 27.11.2020

Product code: 19560600

Page 4 of 9

### Advice on protection against fire and explosion

Vapours can form explosive mixtures with air.  
Keep away from sources of ignition - No smoking.  
Take precautionary measures against static discharges.

### Further information on handling

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

### 7.3. Specific end use(s)

Please refer to our internet website for more information: [www.renfert.com](http://www.renfert.com)

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

### 8.2. Exposure controls

#### Appropriate engineering controls

Safe handling: see section 7

#### Protective and hygiene measures

Do not breathe vapour.  
Avoid contact with skin, eyes and clothes.  
Wash hands before breaks and after work.  
Keep away from food, drink and animal feedingstuffs.

#### Eye/face protection

Wear eye/face protection.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Suitable material: NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

Thickness of the glove material: 0,5 mm

Breakthrough time: >= 60 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**die:master duo 1956 0600**

Revision date: 27.11.2020

Product code: 19560600

Page 5 of 9

### Respiratory protection

Use only in well-ventilated areas.  
Usually no personal respiratory protection necessary.

### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: Liquid  
Colour: colourless  
Odour: characteristic

#### Test method

pH-Value: not applicable

### Changes in the physical state

Melting point: not determined  
Boiling point or initial boiling point and boiling range: 79 °C  
Flash point: - 5 °C DIN 51755 (cc)

### Flammability

Solid/liquid: not applicable  
Gas: not applicable

### Explosive properties

not explosive.  
Vapours can form explosive mixtures with air.

Lower explosion limits: 1,2 vol. %  
Upper explosion limits: 11,5 vol. %  
Auto-ignition temperature: 370 °C

### Self-ignition temperature

Solid: not applicable  
Gas: not applicable

Decomposition temperature: not determined

Vapour pressure: 101 hPa  
(at 20 °C)

Density (at 20 °C): 0,78 - 0,88 g/cm<sup>3</sup>

Water solubility: Immiscible

Partition coefficient n-octanol/water: not determined

Viscosity / dynamic: not determined

Viscosity / kinematic: not determined

Evaporation rate: not determined

### 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Vapours can form explosive mixtures with air.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**die:master duo 1956 0600**

Revision date: 27.11.2020

Product code: 19560600

Page 6 of 9

### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5. Incompatible materials

No special measures are necessary.

### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **Irritation and corrosivity**

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### **Sensitising effects**

Based on available data, the classification criteria are not met.

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

May cause drowsiness or dizziness. (butanone)

#### **STOT-repeated exposure**

Repeated exposure may cause skin dryness or cracking.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### **Further information**

The product has not been tested. The statement is derived from the properties of the single components.

## SECTION 12: Ecological information

### 12.1. Toxicity

There are no data available on the mixture itself.

### 12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
78-93-3	butanone				
		OECD 301D	98 %	28	
	Readily biodegradable (according to OECD criteria).				

### 12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

### 12.4. Mobility in soil

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**die:master duo 1956 0600**

Revision date: 27.11.2020

Product code: 19560600

Page 7 of 9

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.7. Other adverse effects**

No information available.

**Further information**

Do not allow uncontrolled discharge of product into the environment.

The product has not been tested. The statement is derived from the properties of the single components.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Send to a hazardous waste incinerator facility under observation of official regulations .

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**List of Wastes Code - residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** FARBE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3

**Marine transport (IMDG)**

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** PAINT  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Marine pollutant: no

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** PAINT  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

Revision date: 27.11.2020

**die:master duo 1956 0600**

Product code: 19560600

Page 8 of 9

Hazard label: 3

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Further information: see section 6, 7, 8

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

2004/42/EC (VOC): 749,3 g/l

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

**Additional information**

REGULATION (EC) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on substances that deplete the ozone layer: not applicable

REGULATION (EU) 2019/1021 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on persistent organic pollutants  
: not applicable

REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the export and import of hazardous chemicals: not applicable

**SECTION 16: Other information****Changes**

Abs. 11, 12, 15, 16 \* Data changed compared with the previous version

**Abbreviations and acronyms**

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LD50: lethal dose, 50%

LC50: lethal concentration, 50%

EC50: half maximal effective concentration

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

VOC: volatile organic compound(s)



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**die:master duo 1956 0600**

Revision date: 27.11.2020

Product code: 19560600

Page 9 of 9

**Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Restricted to professional users.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**die:master thinner 1956 0700**

Revision date: 29.11.2020

Product code: 19560700

Page 1 of 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

die:master thinner 1956 0700

**Further trade names**

contained in:

1956 0800 die:master Set red

1956 0900 die:master Set blue

1956 1000 die:master Set gold/silver

1957 1000 die:master Set ivory

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

die:master thinner

**Uses advised against**

No information available.

**1.3. Details of the supplier of the safety data sheet**

Company name:	Renfert GmbH	
Street:	Untere Giesswiesen 2	
Place:	D-78247 Hilzingen	
Telephone:	+49 7731 8208-0	Telefax: +49 7731 8208-70
e-mail:	info@renfert.com	
Contact person:	Frau Andris	
e-mail:	silke.andris@renfert.com	
Internet:	www.renfert.com	

**1.4. Emergency telephone number:**

GB: 0044 151 951 3317 (Health and Safety Executive (HSE) Chemicals) | USA: 800-222-1222 (National Poison Control number) | CA: British Columbia: 800-567-8911 or 604-682-5050 Alberta: 1-800-332-1414 or 944-1414 Saskatchewan: 1-866-454-1212 Manitoba: 1-855-776-4766 Ontario: 1-800-268-9017 Quebec: 1-800-463-5060 New Brunswick: 911 New Foundland: 1-866-727-1110 Northwest Territories: 1-800-332-1414 Nova Scotia: 1-800-565-8161 | AU: 13 11 26 | ZA: 021 938 6084 (Office Hours) or 021 931 6129 (24 Hours)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

**2.2. Label elements****Regulation (EC) No. 1272/2008**

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**die:master thinner 1956 0700**

Revision date: 29.11.2020

Product code: 19560700

Page 2 of 9

## Hazard components for labelling

butanone  
pentan-3-one  
n-butyl acetate

**Signal word:** Danger

## Pictograms:



## Hazard statements

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.

## Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves and eye/face protection.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

## Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

## 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Solvents/Thinner

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
78-93-3	butanone			50 - 70 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
96-22-0	pentan-3-one			20 - 40%
	202-490-3	606-006-00-5	01-2119531111-60	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3, STOT SE 3; H225 H319 H335 H336 EUH066			
123-86-4	n-butyl acetate			5 - 15%
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			

Full text of H and EUH statements: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**die:master thinner 1956 0700**

Revision date: 29.11.2020

Product code: 19560700

Page 3 of 9

**General information**

Remove contaminated, saturated clothing immediately.

**After inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**After contact with skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

**After contact with eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**After ingestion**

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. When in doubt or if symptoms are observed, get medical advice.

**4.2. Most important symptoms and effects, both acute and delayed**

The following symptoms may occur: Vapours may cause drowsiness and dizziness. Processing vapours can irritate the respiratory tracts, skin and eyes. Repeated exposure may cause skin dryness or cracking.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Extinguishing powder, Carbon dioxide (CO<sub>2</sub>), alcohol resistant foam, Water spray jet

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Vapours can form explosive mixtures with air.

Thermal decomposition can lead to the escape of irritating gases and vapours.

**5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation.

Use personal protection equipment.

Remove all sources of ignition.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**die:master thinner 1956 0700**

Revision date: 29.11.2020

Product code: 19560700

Page 4 of 9

## Advice on safe handling

Use only in well-ventilated areas.  
Avoid contact with eyes and skin.  
When using do not eat, drink or smoke.

## Advice on protection against fire and explosion

Vapours can form explosive mixtures with air.  
Keep away from sources of ignition - No smoking.  
Take precautionary measures against static discharges.

## Further information on handling

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

## 7.3. Specific end use(s)

Please refer to our internet website for more information: [www.renfert.com](http://www.renfert.com)

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
96-22-0	Pentan-3-one	200	716		TWA (8 h)	WEL
		250	895		STEL (15 min)	WEL

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

### 8.2. Exposure controls

#### Appropriate engineering controls

Safe handling: see section 7

#### Protective and hygiene measures

Do not breathe vapour.  
Avoid contact with skin, eyes and clothes.  
Wash hands before breaks and after work.  
Keep away from food, drink and animal feedingstuffs.

#### Eye/face protection

Wear eye/face protection.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.  
Suitable material: NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**die:master thinner 1956 0700**

Revision date: 29.11.2020

Product code: 19560700

Page 5 of 9

Thickness of the glove material: 0,5 mm

Breakthrough time: >= 60 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

## Respiratory protection

Use only in well-ventilated areas.

Usually no personal respirative protection necessary.

## Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless
Odour:	characteristic

pH-Value:	not applicable	<b>Test method</b>
-----------	----------------	--------------------

#### Changes in the physical state

Melting point:	not determined
----------------	----------------

Initial boiling point and boiling range:	79 °C
--	-------

Flash point:	- 1,5 °C	DIN 51755 (cc)
--------------	----------	----------------

#### Flammability

Solid:	not applicable
--------	----------------

Gas:	not applicable
------	----------------

#### Explosive properties

not explosive.

Vapours can form explosive mixtures with air.

Lower explosion limits:	1,2 vol. %
-------------------------	------------

Upper explosion limits:	11,5 vol. %
-------------------------	-------------

Ignition temperature:	370 °C
-----------------------	--------

#### Auto-ignition temperature

Solid:	not applicable
--------	----------------

Gas:	not applicable
------	----------------

Decomposition temperature:	not determined
----------------------------	----------------

Vapour pressure: (at 20 °C)	105 hPa
--------------------------------	---------

Density (at 20 °C):	0,7 - 0,9 g/cm <sup>3</sup>
---------------------	-----------------------------

Water solubility:	Immiscible
-------------------	------------

Partition coefficient:	not determined
------------------------	----------------

Viscosity / dynamic:	not determined
----------------------	----------------

Viscosity / kinematic:	not determined
------------------------	----------------

Vapour density:	not determined
-----------------	----------------

Evaporation rate:	not determined
-------------------	----------------

Solvent content:	100%
------------------	------

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**die:master thinner 1956 0700**

Revision date: 29.11.2020

Product code: 19560700

Page 6 of 9

## 9.2. Other information

Solid content: 0 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Vapours can form explosive mixtures with air.

### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **Irritation and corrosivity**

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### **Sensitising effects**

Based on available data, the classification criteria are not met.

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

May cause respiratory irritation. (pentan-3-one)

May cause drowsiness or dizziness. (butanone; pentan-3-one)

#### **STOT-repeated exposure**

Repeated exposure may cause skin dryness or cracking.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### **Further information**

The product has not been tested. The statement is derived from the properties of the single components.

## SECTION 12: Ecological information

### 12.1. Toxicity

There are no data available on the mixture itself.

### 12.2. Persistence and degradability

There are no data available on the mixture itself.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

**die:master thinner 1956 0700**

Revision date: 29.11.2020

Product code: 19560700

Page 7 of 9

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
78-93-3	butanone			
	OECD 301D	98 %	28	
	Readily biodegradable (according to OECD criteria).			

## 12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
96-22-0	pentan-3-one	0,82

## 12.4. Mobility in soil

There are no data available on the mixture itself.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Other adverse effects

No information available.

## Further information

The product has not been tested. The statement is derived from the properties of the single components. Do not allow uncontrolled discharge of product into the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Send to a hazardous waste incinerator facility under observation of official regulations .

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

#### List of Wastes Code - residues/unused products

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste

#### Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1263
<b>14.2. UN proper shipping name:</b>	FARBZUBEHÖRSTOFFE
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



### Marine transport (IMDG)

<b>14.1. UN number:</b>	UN 1263
-------------------------	---------



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**die:master thinner                    1956 0700**

Revision date: 29.11.2020

Product code: 19560700

Page 8 of 9

**14.2. UN proper shipping name:** PAINT RELATED MATERIAL

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** II

Hazard label: 3



Marine pollutant: no

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1263

**14.2. UN proper shipping name:** PAINT RELATED MATERIAL

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** II

Hazard label: 3



### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

### 14.6. Special precautions for user

Additional information: see section 6, 7, 8

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: Flüssige Stoffe oder Gemische, die Kriterien für eine der folgenden in Anhang I der Verordnung (EG)

2004/42/EC (VOC): 100 %

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

#### Additional information

REGULATION (EC) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on substances that deplete the ozone layer: not applicable

REGULATION (EU) 2019/1021 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on persistent organic pollutants  
: not applicable

REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the export and import of hazardous chemicals: not applicable

## SECTION 16: Other information

### Changes

Abs. 11, 12, 15, 16 \* Data changed compared with the previous version

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**die:master thinner 1956 0700**

Revision date: 29.11.2020

Product code: 19560700

Page 9 of 9

**Abbreviations and acronyms**

PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 LD50: lethal dose, 50%  
 LC50: lethal concentration, 50%  
 EC50: half maximal effective concentration  
 ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 RID: Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 IMDG: International Maritime Code for Dangerous Goods  
 ICAO: International Civil Aviation Organization  
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
 VOC: volatile organic compound(s)

**Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method

**Relevant H and EUH statements (number and full text)**

H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H319 Causes serious eye irritation.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 EUH066 Repeated exposure may cause skin dryness or cracking.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Restricted to professional users.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*