

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Luxatemp Plus**

Revision date: 15.04.2021

Product code: 1300

Page 1 of 5

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Luxatemp Plus

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Uses advised against**

pregnant or breastfeeding people should not work with hazardous substances

**1.3. Details of the supplier of the safety data sheet**

Company name:	DMG Chemisch-Pharmazeutische Fabrik GmbH	
Street:	Elbgaustraße 248	
Place:	D-22547 Hamburg	
Telephone:	+49. (0) 40. 84006-0	Telefax: +49. (0) 40. 84006-222
e-mail:	info@dmg-dental.com	
Internet:	www.dmg-dental.com	

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

May cause respiratory irritation.

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

**2.2. Label elements****Regulation (EC) No 1272/2008**

Signal word: Warning

Pictograms:

**Hazard statements**

H335	May cause respiratory irritation.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

**Precautionary statements**

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302+P352	IF ON SKIN: Wash with plenty of water.

**2.3. Other hazards**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

**SECTION 3: Composition/information on ingredients**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Luxatemp Plus**

Revision date: 15.04.2021

Product code: 1300

Page 2 of 5

**3.2. Mixtures****Chemical characterization**

chemical characterization (preparation): Acrylate.-resin.

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
41637-38-1	Dimethacrylate Resin			35-45 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Chronic 4; H315 H319 H317 H335 H413			

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures****After inhalation**

Avoid exposure. Provide fresh air. Move victim to fresh air. Put victim at rest and keep warm.

**After contact with skin**

After contact with skin, wash immediately with: Water and soap.

**After contact with eyes**

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

**After ingestion**

Medical treatment necessary.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO<sub>2</sub>).**Unsuitable extinguishing media**

High power water jet.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

**6.3. Methods and material for containment and cleaning up****Other information**

Take up mechanically. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Luxatemp Plus**

Revision date: 15.04.2021

Product code: 1300

Page 3 of 5

**Advice on general occupational hygiene**

When using do not eat or drink.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Store only in original container.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Additional advice on limit values**

To date, no national critical limit values exist.

**8.2. Exposure controls****Individual protection measures, such as personal protective equipment****Eye/face protection**

Tightly sealed safety glasses.

**Hand protection**

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

**Respiratory protection**

The following must be prevented: inhalation.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Paste	
Colour:	characteristic	
Odour:	ester	
Boiling point or initial boiling point and boiling range:		>250 °C
Flash point:		>150 °C
Auto-ignition temperature:		>380 °C
pH-Value (at 20 °C):		ca. 7
Water solubility:		10 g/L
Vapour pressure:		1 hPa
(at 20 °C)		
Density:		1,5 g/cm <sup>3</sup>
Relative vapour density:		1
point of decomposition:		200 °C

**SECTION 10: Stability and reactivity****10.4. Conditions to avoid**

heat. Light.

Decomposition takes place from temperatures above: 200 °C

Decomposition under formation of: Acrylate.

**10.5. Incompatible materials**

radical former. Keep away from strong acids, leachates, heavy metal salts and reducing materials.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Luxatemp Plus**

Revision date: 15.04.2021

Product code: 1300

Page 4 of 5

**10.6. Hazardous decomposition products**

In case of fire may be liberated: Gas / vapours, irritant. (Acrylate., pungent). nitrogen oxides (NOx).

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

LD50: Rat 5000 mg/kg

**Irritation and corrosivity**

Frequently or prolonged contact with skin may cause dermal irritation.

Irritant effect on the eye:

**Additional information on tests**

Contains Methacrylic esters.: May produce an allergic reaction.

**SECTION 12: Ecological information****12.1. Toxicity**

Acute fish toxicity LC50: >360 mg/l/48h

**12.2. Persistence and degradability**

Preparation not tested.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Paste: Carry out a burning of hazardous waste according to official regulations.

**List of Wastes Code - residues/unused products**

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances; hazardous waste

**SECTION 14: Transport information****Other applicable information**

No dangerous good in sense of these transport regulations.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information****SECTION 16: Other information**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Luxatemp Plus**

Revision date: 15.04.2021

Product code: 1300

Page 5 of 5

**Relevant H and EUH statements (number and full text)**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H413	May cause long lasting harmful effects to aquatic life.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*